

BOILER 150



ABOUT THE RANGE

ICS Cool Energy's Boiler 150 are housed in a steel container providing increased security and protection from the weather. The container also aids with portability as the unit can easily be positioned with a fork-lift truck or crane and connected to a customer's system ensuring a fast rental set-up.

The compact system is powerful in design offering low temperature hot water for demanding requirements. Rapid and secure connections are made using flexible high temp hoses fitted with PN16 flanges. Available in low and high pressure versions capable of operating up to 3 Bar pressure and temperatures up to 90°C.

UNIT SPECIFICATION

| | |
|--------------------------------------|--------------------------|
| Dimensions (W x D x H) | 2,690 x 1,200 x 2,275 mm |
| Weight (Empty) | 1530kg |
| Heating Power | 150kW |
| Heating Mode | 20°C - 90°C |
| Temperature (Supply/Return) | 90°C - 70°C |
| Water Connections | 2"/DN 50 |
| Boiler Fuel Consumption at full load | |
| Diesel: | 15.5 Litres / hr |
| Gas: | 17.4 m ³ / hr |
| Part Load turn down | |
| Diesel: | 2 : 1 |
| Gas: | 6 : 1 |
| Safety Valve (standard) | 3 Bar |
| Expansion Vessel | 200 Litre |
| Power Supply (V/PH/Hz) | 230/1/50 |
| Electrical Supply | CEE 16 A |

CONTACT

Bel ons op
+31 (0)88 - 258 2580 of
 bezoek onze website
www.icscoolenergy.nl

info@icscoolenergy.nl