



BOILER 600



ABOUT THE RANGE

ICS Cool Energy's Boiler 600 are contained within a steel container enabling external siting and increased protection from environmental elements. The container also aids with portability as the unit can easily be positioned with a fork-lift unit and connected to a customers system, ensuring a fast rental set-up.

The units are designed for reliable and safe operation with flexible hoses resistant up to 7Bar pressure and temperatures up to 100°C. Furthermore the units feature safety devices and system protection.

Other features within the unit include a diaphragm expansion tank and frost protection.

UNIT SPECIFICATION

Dimensions (W x D x H)	4,550 x 2,440 x 2,450 mm
Weight (Empty)	5000 kg
Heating Power	600kW
Heating Mode	20°C - 90 °C
Temperature (Supply/Return)	90/70 °C
Water Connections	4"/DN 100
Boiler Fuel Consumption at full load	
Diesel:	62 Litres / hr
Gas:	64.2 m ³ / hr
Part Load turn down	
Diesel:	2 : 1
Gas:	6 : 1
Safety Valve	3 Bar
Expansion Vessel	500 Litre
Power Supply (V/PH/Hz)	400/3/50
Electrical Supply	CEE 32 A

CONTACT

Bel ons op
+31 (0)88 - 258 2580 of
bezoek onze website
www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and continuous improvement without notice

© ICS Cool Energy. All rights reserved.

THE TEMPERATURE CONTROL SPECIALISTS.
VERHUUR. VERKOOP. SERVICE.

WWW.ICSCOOLENERGY.NL