

BOILER 600 V2



ABOUT THE RANGE

ICS Cool Energy's Boiler 600 V2 are housed in a steel container providing increased security and protection from the weather. The container also aids with portability as the unit can easily be positioned with a fork-lift truck or crane and connected to a customer's system ensuring a fast rental set-up.

The compact system is powerful in design offering low temperature hot water for demanding requirements. Rapid and secure connections are made using flexible high temp hoses fitted with PN16 flanges. Available in low and high pressure versions capable of operating up to 4 Bar pressure and temperatures up to 90°C.

UNIT SPECIFICATION

Dimensions (W x D x H)	3790 x 1710 x 2325mm
Weight (Empty)	3200kg
Heating Power	560kW
Heating Mode	20°C - 90°C
Temperature (Supply/Return)	90/70 °C
Water Connections	2 1/2" /DN65
Boiler Fuel Consumption at full load	
Diesel:	61.7 litres/hr
Gas:	67m3/hr
Part Load turn down	
Diesel:	2 : 1
Gas:	6 : 1
Safety Valve (standard)	4 Bar
Expansion Vessel	500 Litre
Power Supply (V/PH/Hz)	400/3/50
Electrical Supply	16A

CONTACT US

Call us free on
0800 840 4210 or
visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com