



ABOUT THE CHILLER

The Chiller 3, which provides a reduced footprint, lower power usage and is Eurovent certified, is part of a 10 model range capable of offering between 1kW and 50kW of cooling.

The chillers all contain a circulation pump and thermal buffer tank capable of receiving variable load conditions and providing stable return temperatures.

The units can be supplied with ferrous or non-ferrous circuit, together with a wide range of connecting valves and hoses to help connect on to customers specific systems.

The ranges have been designed to help provide cooling for the following uses:

- R&D testing for long or short term trials
- Plastics and Rubber production
- Food storage and packaging
- Laser applications
- Jacketed vessels and tank cooling
- Air compressor cooling

THE ICS COOL ENERGY PORTFOLIO

ICS Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW – 1,000kW units.
- Water-cooled rental chiller range from 7.5kW – 1,000kW units.
- Air handling units & fan coils from 5kW – 500kW duties.
- Air conditioning units from 1.3kW – 350kW units.
- Low temperature chillers (-40°C) and fan coils (0°C air off).

- Dehumidifiers (desiccant & electric) 200-10,000m³/hr.
- Generator Power with 20KVA – 800KVA, fuel tanks and management.
- Air distribution (flexible ducting and perforated air socks).
- Hot water generators and boilers from 25kW – 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.

CONTACT

Bel ons op
+31 (0)88 - 258 2580 of
 bezoek onze website
www.icscoolenergy.nl

info@icscoolenergy.nl



ics cool energy

TECHNICAL CHILLER 3

Chiller (LxWxH)	550 x 600 x 772
Stacking Frame (LxWxH)	898 x 925 x 1600
Weight kg (including frame)	132
Water hoses	½" Hose Tail
Cooling Capacity kW	3
Compressor (Scroll)	1
Refrigerant (Zero ozone depletion potential) HFC	R 407 C / 410 A
Fluid Flow l/m min/max	0.55/0.75
Pump Pressure Bar l/m max/min	3.0/1.4
Tank l	25
Delta T min/max K	4-10
Max Working Pressure Bar	6
Max Power Absorbed kW	1.36
Electrical Supply Voltage Phase V	240
Max Current Absorbed A	9
Chiller Power Connections Amp	CEE 16 A
Sound Pressure Level	48.3

CONTACT

Bel ons op
+31 (0)88 - 258 2580 of
bezoek onze website
www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and
continuous improvement without notice

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
VERHUUR. VERKOOP. SERVICE.**

WWW.ICSCOOLENERGY.NL