



COOL STORE 3006



ABOUT THE CHILLER

ICS Cool Energy's container cold stores are specially built and ideal for customers needing on site chilling or deep frozen storage. The temperature range of these units are -25°C to $+15^{\circ}\text{C}$, they're powerful in design and can offer instant additional cold storage to a site from an external location.

The units feature stainless steel or one-piece GRP internal panels. Lighting, rub rails and a high strength hard wearing non-slip floor is supplied as standard. Externally, the units have smooth aluminium side panels and a white roof giving good levels of heat reflection, furthermore the units feature fork lift pockets making them easy to position externally. The system controls feature a temperature display and de-frost indicator. Performance data is logged to monitor cold store temperatures and de-frost logs.

TECHNICAL

External Dimensions (L x W x H)	6,055 x 2,950 x 2,765mm
Internal Dimensions (L x W x H)	4,810 x 2,580 x 2,240mm
Weight	2.15 tons
Internal Stacking Height	1,850mm
Door Dimensions (W x H)	1,400 x 2,100mm
Height to Threshold	330mm
Insulation Thickness	170mm
Power	5kW @ -30°C evaporation
Temperature Range	-25°C to $+15^{\circ}\text{C}$
Refrigerant	R404A 6.5kG
Electrical Supply	415/3/50 neutral & earth
Electrical Connection	BS4343 plug 32amp 5 pin plug
Pallet Capacity	12 (Euro: 800 x 1,200mm)
Volume @ 10m	67dB (A)

STANDARD FEATURES

Access Ramp	Emergency Door Release
Strip Curtain	Personnel Alarm
LED Lighting	Complies with HACCP hygiene and GMP Standards

CONTACT US

Call us free on
0800 840 4210 or
visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM