



SPOT COOLER 6.7



ABOUT THE UNIT

The Spot Cooler 6.7 (23,000 Btu/hr) is a freestanding unit and can direct cold air to specific areas by utilising the twin adjustable air ducts (6"/150mm) situated in the front of the unit. Additional hoses can be supplied to increase the hose length to a maximum 1.25 metres

SIMPLE TO USE

This single fan SPOT COOLER with large volume air movement of 1,170m³/hr is ideally suited to cool server rooms, production areas and workplaces.

The unit has been designed for a fast rental installation and start up, operates from a standard 13amp single-phase supply and has a single 6" heat rejection hose, together with a 12 litre condensate container. In addition to this, the unit is entirely portable and has castors with brakes.

REJECT THE HEAT COLLECTED

Enters via a local window either into another room or warehouse area, to ceiling void or to a place where you can re-use the heat collected.

Dimensions (LxDxH)	mm	690 x 530 x 1,080
Weight	Kg	86
Air Connections	mm	2 x 6"/150
Air Flow	m ³ /hr	1,170
Exhaust Duct	mm	6"/150 (max 6m)
Current Consumption	Amps	<9A
Power Supply	-	230/1/150 (1.5mm ²)
Max Power Absorbed	kW	2.0
Power Connections	-	13amp standard plug
Power Sound Level	dB(A)	66 @ 10m (max fan speed)
Nominal Cooling duty	kW	6.7 @ 22°C in 28°C ambient

CONTACT US

Call us free on
0800 840 4210 or
 visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
 SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM