

## **BOILER 1300**



## **ABOUT THE RANGE**

ICS Cool Energy's Boiler 1300 are contained within a steel container enabling external siting and increased protection from environmental elements. The container also aids with portability as the unit can easily be positioned with a fork-lift unit and connected to a customers system, ensuring a fast rental set-up.

The units are designed for reliable and safe operation with flexible hoses resistant up to 7Bar pressure and temperatures up to 100°C. Furthermore the units feature safety devices and system protection.

Other features within the unit include a diaphragm expansion tank and frost protection.

## UNIT SPECIFICATION

Dimensions (W x D x H)	6,058 x 2,435 x 2,590 mm
Weight (Empty)	6100kg
Heating Power	1300kW
Heating Mode	55 - 90 °C
Temperature (Supply/Return)	90/70 °C
Water Connections	6" Dn150
Boiler Fuel Consumption at full load Diesel:	143 Litres / hr
Part Load turn down Diesel:	2 : 1
Safety Valve	6 Bar
Expansion Vessel	500 Litre
Power Supply	400/3/50
Electrical Supply	CEE 32 A

CONTACT

Bel ons op +31 (0)88 - 258 2580 of bezoek onze website www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and continuous improvement without notice

© ICS Cool Energy. All rights reserved.