



## ABOUT THE CHILLER

ICS Cool Energy's Chiller 760 has the latest energy-saving Bitzer screw compressors (2), offering a wide temperature range of -10°C to 15°C water leaving temperature and 50% - 100% capacity control.

The chiller is fully F-Gas Certified and offers the zero ozone depleting HFC refrigerant R134a and manufactured to the latest environmental ISO14001 controls.

With low noise (61dB(a)) operation and compact footprint, the Chiller 760 unit is currently the smallest chiller/kW available in the UK.

## CONTACT US

Call us free on  
**0800 840 4210** or  
visit our website  
[www.icscoolenergy.com](http://www.icscoolenergy.com)

Depots Nationwide

[hire@icscoolenergy.com](mailto:hire@icscoolenergy.com)

## THE ICS COOL ENERGY PORTFOLIO

ICS Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW – 1,000kW units.
- Water-cooled rental chiller range from 7.5kW – 1,000kW units.
- Air handling units & fan coils from 5kW – 500kW duties.
- Air conditioning units from 1.3kW – 350kW units.
- Low temperature chillers (-40°C) and fan coils (0°C air off).

- Dehumidifiers (desiccant & electric) 200-10,000m<sup>3</sup>/hr.
- Generator Power with 20KVA – 800KVA, fuel tanks and management.
- Air distribution (flexible ducting and perforated air socks).
- Hot water generators and boilers from 25kW – 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.



## TECHNICAL CHILLER 760

### PERFORMANCE DATA @ DESIGN CONDITIONS

Cooling Capacity	kW	760
Operation Fluid Temperature IN/OUT	°C	12/7
Design Ambient Temperature	°C	30
Fluid Flow Min/Max	m <sup>3</sup> /hr	50/137
	l/s	13.9/38.0

### OPERATING LIMITS

Min/Max Ambient Temperature	°C	-18/43
Min/Max Leaving Fluid Temperature	°C	-10/15
Evaporator Pressure Drop	kPa	46
Max Working Pressure	kPa	1,000
Evaporator Water Volume	1	200

### ELECTRICAL DATA

Electrical Supply Voltage 3 phase	V	400
Chiller Power Connections		12mm lugs
Cable Connection	M12	3 core + earth, no neutral
Max Power Absorbed	kW	266
Max Current Absorbed (+7°C)	A	500
Starting Current (Max)	A	579
Pre-Heating Crankcase Supply	V	230
AUX Supply Connection for pump		63A Ceeform
Recommended Generator Set	kVA	450
Control System		W3000

### REFRIGERANT SYSTEM

Bitzer Screw Compressors (2 circuits) 6 step capacity		2
(50-100% Variable Capacity)		
Refrigerant (Zero ozone depletion potential)	HFC	R134a

### FANS

Total Number	1.1kW each	12
Total Airflow	m <sup>3</sup> /hr	32.3

### SOUND DATA

Sound Pressure Level at 10 metres (ISO3744) (see separate guide attached for octave band detail)	dB(A)	61
--	-------	----

### PHYSICAL DATA

Overall Length	mm	5,810
Overall Width	mm	2,310
Overall Height	mm	2,400
Weight	kg	7,500
Fluid Coupling Size	mm/inch	150/11
Fluid Coupling Type	choice	PN16 Flange
IPLV Rating		4.24
ESEER Rating		3.73

## CONTACT US

Call us free on  
**0800 840 4210** or  
visit our website  
[www.icscoolenergy.com](http://www.icscoolenergy.com)

Depots Nationwide

[hire@icscoolenergy.com](mailto:hire@icscoolenergy.com)

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.


© ICS Cool Energy. All rights reserved.

THE TEMPERATURE CONTROL SPECIALISTS.  
SALES. HIRE. SERVICE.

[WWW.ICSCOOLENERGY.COM](http://WWW.ICSCOOLENERGY.COM)



## PERFORMANCE



## SOUND LEVELS

Measurements are taken in accordance with the standard ISO 3744.

Sound pressure average value obtained in free field on a reflective surface at a distance of 10m from the longer side of the machine at a height of 1.6m +/- 2 under full load in normal conditions.

For measurements closer than 10m add the following: 5m +6, 3m +10 and 1m +15

OCTAVE BANDS (H3)							SOUND PRESSURE	
63	125	250	500	1000	2000	4000	8000	
SOUND POWER LEVEL dB(A)								dB(A) 10m
54	53	56	58	59	47	37	29	61.0

Additional Services: ICS Cool Energy can provide attenuated equipment and services to help further reduce the impact of our equipment to help meet your specific site requirements.

## SUB 5°C WATER APPLICATIONS

When installing a chiller and/or air handling piece of equipment, we would recommend the use of the following mix of Glycol for the systems total volume of fluid. This will protect the equipment against internal freezing and failure (e.g. 200 litre volume @ 0 °C foodsafe equals 30 litres of Glycol and 170 litres of water). Weekly checks should be made by the site maintenance engineer/manager to ensure the correct mix is present in the system.

Water Temperature			5 °C	0 °C	-5 °C	-10 °C	-15 °C
Industrial Grade	Mono Ethylene Glycol	% Mix	5	10	20	25	30
Foodsafe Grade	Mono Propylene Glycol	% Mix	10	15	20	25	30
Bio Foodsafe Grade (made from vegetable extracts)	Biodegradable Glycol	% Mix	10	15	20	25	30

Glycol can be purchased from ICS Cool Energy in 25 litre, 205 litre and 1,000 drums.

## CONTACT US

Call us free on  
**0800 840 4210** or  
visit our website  
[www.icscoolenergy.com](http://www.icscoolenergy.com)

Depots Nationwide

[hire@icscoolenergy.com](mailto:hire@icscoolenergy.com)

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

© ICS Cool Energy. All rights reserved.

THE TEMPERATURE CONTROL SPECIALISTS.  
SALES. HIRE. SERVICE.

[WWW.ICSCOOLENERGY.COM](http://WWW.ICSCOOLENERGY.COM)