



COLD STORE 10



ABOUT THE CHILLER

ICS Cool Energy's Cold Store 10 has been designed & built with the user in mind offering continuous reliability, optimal performance & low running costs. The Cold Store 10 has been designed to offer cold storage solutions at a width of 2 pallets with flush fitting machines to prevent any loss of internal capacity. Units are available from stock for nationwide delivery. ICS Cool Energy's Cold Store 10 provides economical, powerful cooling with fault free operation providing the ideal temperature to store your products, with further eco mode operation to minimise power use & self diagnostic capabilities providing additional peace of mind.

All Cold Store 10 containers are manufactured in accordance with the latest guidelines & CFC legislation. Standard features include:

- High insulation value
- Anti slip aluminium flooring
- Easy open door with inbuilt lock
- 220V LED fluorescent internal lights
- Internal door opening
- Person trapped alarm
- Modern power efficient machinery (many with datalogger)
- -40°C to +30°C range (subject to model)
- Maximum air temperature fluctuation 0.25°C from set point after pull down (most models)
- Hygienic stainless steel interior panels / aluminium floor
- Robust MGSS stainless steel exterior
- Internal fork truck / motorised pallet lifter use permitted
- Ramp to 500kg (heavy duty ramps available)
- 380V/440V 3 phase heavy duty cable with 5 pin/32A CE plug
- Average age of our rental fleet is less than 5 years
- Foundations or even ground is NOT required

CONTACT US

Call us free on
0800 840 4210 or
visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

Revision 3 12/05/22

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM



COLD STORE 10

TECHNICAL

EXTERNAL DIMENSIONS		
Length	2,991 mm	9'6"
Width	2,438 mm	8'
Height	2,591 mm	8'6"

INTERNAL DIMENSIONS		
Length	2,343 mm	7'8"
Width	2,058 mm	6'9"
Height	2,179 mm	7'2"

OPENINGS		
Width	1,100 mm	3'7"
Height	2,000 mm	6'7"

Internal Volume	10.5m ³	371 cu ft
Max Payload	7,700 kg	16,980 lb
Max Air Temp Fluctuation	+/- 0.25°C	
Temperature Range	-40°C to +30°C	
Max Running Current	17A	
Power Connection	380/440V 3 phase heavy duty cable with 5pin/32A CE plug	

CONTACT US

Call us free on
0800 840 4210 or
 visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

Revision 3 12/05/22

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
 SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM