

COLD STORE 20



ABOUT THE COLD STORE

ICS Cool Energy's Cold Store 20 has been designed ϑ built with the user in mind offering continuous reliability, optimal performance ϑ low running costs. The Cold Store 20 has been designed to offer cold storage solutions at a width of 2 pallets with flush fitting machines to prevent any loss of internal capacity. Units are available from stock for nationwide delivery. ICS Cool Energy's Cold Store 20 provides economical, powerful cooling with fault free operation providing the ideal temperature to store your products, with further eco mode operation to minimise power use ϑ self diagnostic capabilities providing additional peace of mind.

All Cold Store 20 containers are manufactured in accordance with the latest guidelines θ CFC legislation. Standard features include:

- High insulation value
- Anti slip aluminium flooring
- Easy open door with inbuilt lock
- 220V LED fluorescent internal lights
- Internal door opening
- Person trapped alarm
- Modern power efficient machinery (many with datalogger)
- -40°C to +30°C range (subject to model)
- Maximum air temperature fluctuation 0.25°C from set point after pull down (most models)
- Hygienic stainless steel interior panels / aluminium floor
- Robust MGSS stainless steel exterior
- Internal fork truck / motorised pallet lifter use permitted
- Ramp to 500kg (heavy duty ramps available)
- 380V/440V 3 phase heavy duty cable with 5 pin/32A CE plug
- Average age of our rental fleet is less than 5 years
- Foundations or even ground is NOT required

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and

© ICS Cool Energy. All rights reserved.

CONTACT US

www.icscoolenergy.com

hire@icscoolenergy.com

Call us free on

0800 840 4210 or visit our website

Depots Nationwide



COLD STORE 20 TECHNICAL

EXTERNAL DIMENSIONS		
Length	6,058 mm	19'11''
Width	2,438 mm	8′
Height	2,591 mm	8'6"
INTERNAL DIMENSIONS		
Length	5,450 mm	17'11"
Width	2,284 mm	7'6"
Height	2,298 mm	7'7''
OPENINGS		
Width	2,290 mm	7'6"
Height	2,264 mm	7'5''
Internal Volume	28.6 m³	1,010 cu ft
Max Payload	27,620 kg	60,890 lb
Max Air Temp Fluctuation	+/- 0.25°C	
Temperature Range	-40°C to +30°C	
Max Running Current	17A	
Power Connection	380/440V 3 phase heavy duty cable with 5pin/32A CE plug	

CONTACT US

Call us free on **0800 840 4210** or visit our website www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com