

ELECTRIC BOILER 19A



ABOUT THE UNIT

ICS Cool Energy are pleased to offer a powerful and advanced range of electric hot water packages (HWPE) which are now available to hire. The units are capable of operating with a heat output of 19kW and are compact in design as well as being extremely flexible and durable supporting planned and emergency requirements on a long or short term rental basis.

ICS Cool Energy's Electric Boiler 19A offers a quick user friendly replacement for broken down boilers for factories, hotels, care homes and offices or temporary applications like event catering or temporary accommodation. ICS Cool Energy's Electric Boiler 19A connects directly to sites pre-existing heating system minimising the set up time and restoring heat easily with minimal disruption. Furthermore the units are supplied on lightweight trolleys to aid mobility and enable units to be easily and discretely positioned.

THE ICS COOL ENERGY PORTFOLIO

ICS Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW 1,000kW units.
- Water-cooled rental chiller range from 7.5kW
 1,000kW units.
- Air handling units & fan coils from 5kW 500kW duties.
- Air conditioning units from 1.3kW 350kW
- Low temperature chillers (-40°C) and fan coils (0°C air off).

- Dehumidifiers (desiccant & electric) 200-10,000m3/hr.
- Generator Power with 20KVA 800KVA, fuel tanks and management.
- Air distribution (flexible ducting and perforated air socks).
- Hot water generators and boilers from 25kW 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.

CONTACT

Bel ons op +31 (0)88 - 258 2580 of bezoek onze website www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and continuous improvement without notice

© ICS Cool Energy. All rights reserved.



TECHNICAL ELECTRIC BOILER 19A

Disconsions (W. D. v. II)	600 v FF0 v 1 220 mana
Dimensions (W x D x H)	600 x 550 x 1,220 mm
Weight (Including Trolley)	55kg
Heating Capacity	3 kW (1) 11 kW (2) 19 kW (3)
Temperature Range	20 - 80°C
Control	Digital
Circulation Pump	2 m³/h GN 25/60
Heating Connection	1" Camlock
Volume of Expansion Tank	10 Litre
IP Rating	IP 54
Recommended Operating Pressure	1.5 - 2.0 Bar (Safety Valve is 3.0 Bar)
Power Supply	240/1/50 (1) 415/3/50 (2+3)
Electrical Connection	3 pin domestic (1) CEE 16A (2) CEE 32A (3)

CONTACT

Bel ons op +31 (0)88 - 258 2580 of bezoek onze website www.icscoolenergy.nl

info@icscoolenergy.nl