

FAN COIL 30 - 50



ABOUT THE UNIT

The Fan Coil 30-50 is a light-weight portable unit capable of offering 3,200m³/hr air flow. Air can also be ducted off a 300mm spigot.

The unit requires a water source to the integral coil and has quick release water connections, together with a 13 amp (BS1363) single phase standard power connection.

The fan coil is sited internally and has an adjustable air discharge grill with louvres. The unit is also supplied with an integral condensate pump and air purge facility to assist with commissioning.

THE ICS COOL ENERGY PORTFOLIO

ICS Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW 1,000kW units.
- Water-cooled rental chiller range from 7.5kW 1,000kW units.
- Air handling units & fan coils from 5kW 500kW duties.
- \bullet Air conditioning units from 1.3kW 350kW units.

 \bullet Low temperature chillers (-40°C) and fan coils (0°C air off).

- Dehumidifiers (desiccant & electric) 200-10,000m3/hr.
- Generator Power with 20KVA 800KVA, fuel
- tanks and management.
- Air distribution (flexible ducting and
- perforated air socks).
- Hot water generators and boilers from 25kW 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.

CONTACT

Bel ons op +31 (0)88 - 258 2580 of bezoek onze website www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and continuous improvement without notice

© ICS Cool Energy. All rights reserved.

THE TEMPERATURE CONTROL SPECIALISTS. VERHUUR. VERKOOP. SERVICE.



TECHNICAL FAN COIL 30-50

PERFORMANCE DATA @ DESIGN CONDITIONS

Cooling Capacity	kW	32
Sensible Cooling Capacity	kW	16
Heating Capacity	kW	50

OPERATING LIMITS			
Min Air Off Temperature	°C	10	
Min Air Off Temperature	°C	50	
Water on Coil (min/max)	°C	0/60	
Fluid Pressure Drop	kPa	45	
Max. Working Pressure	Bar	6	
Coil Water Volume	1	10	
Condensate Connection	Hose Tail	1/4"	

ELECTRICAL DATA

Electrical Supply Voltage	V	230/50hz
Power Connections	A	3 Pin
Max Power Absorbed	kW	2
Max Current Absorbed	A	3.6
Starting Current (Max)	A	12
Control System (motorised 3 way valve)	Switch	Automatic Thermostat

AIR LIMITS

Total Number Fans	0.4kW	1
Total Airflow	m³/hr	3,200
	m³/s	0.89
Max Air Throw	m	10

59

SOUND DATA

Sound Pressure Level at 10 metres	dB(A)
(ISO3744)	

PHYSICAL DATA

FILIDICAL DATA		
Overall Length	mm	588
Overall Width	mm	426
Overall Height	mm	1840
Weight (wet)	kg	102
Control System (Motorised 3 way valve)	switch	Automatic Thermostat
Fluid Coupling	Camlock	1"

CONTACT

Bel ons op +31 (0)88 - 258 2580 of bezoek onze website www.icscoolenergy.nl

info@icscoolenergy.nl

All data is subject to change and continuous improvement without notice

© ICS Cool Energy. All rights reserved.