



FAN COIL 50



ABOUT THE UNIT

ICS Cool Energy's Fan Coil 50 Unit is a flexible twin fan unit capable of offering 5,040m³/hr air flow. The unit requires a water source to the integral coil and has quick-release water connections, together with a 16amp single power connection.

The air handler is sited internally and has a removable air discharge at the top. This can be removed to reveal a 600mm spigot to connect flexible ducting to provide air off the unit to specific and remote areas.

The unit is also supplied with a condensate pump and fan speed controller to regulate the air flow.

THE ICS COOL ENERGY PORTFOLIO

ICS Cool Energy can also supply the following equipment:

- Air-cooled rental chiller range from 0.3kW – 1,000kW units.
- Water-cooled rental chiller range from 7.5kW – 1,000kW units.
- Air handling units & fan coils from 5kW – 500kW duties.
- Air conditioning units from 1.3kW – 350kW units.
- Low temperature chillers (-40°C) and fan coils (0°C air off).

- Dehumidifiers (desiccant & electric) 200-10,000m³/hr.
- Generator Power with 20KVA – 800KVA, fuel tanks and management.
- Air distribution (flexible ducting and perforated air socks).
- Hot water generators and boilers from 25kW – 500kW units.
- Heating (office/warehouse) from 3kW to 200kW electric/indirect/heat pump.

We also provide full installation, transportation, lifting and monitoring.

CONTACT US

Call us free on
0800 840 4210 or
visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM



TECHNICAL FAN COIL 50 V2

PERFORMANCE DATA @ DESIGN CONDITIONS

Cooling Capacity	kW	50
Sensible Cooling Capacity	kW	35
Air Off Temperature	°C	20
Air On Temperature	°C	25

OPERATING LIMITS

Min/Max Air Off Temperature	°C	10/30
Fluid Pressure Drop	kPa	36
Max. Working Pressure	Bar	6
Coil Water Volume	l	25
Condensate Connection	Hose Tail	3/8

ELECTRICAL DATA

Electrical Supply Voltage	V	240
Power Connections	A	16 C Forme plug
Max Power Absorbed	kW	2.4
Max Current Absorbed	A	10
Starting Current (Max)	A	14

AIR LIMITS

Total Number Fans	1.2kW each	2
Total Airflow	m ³ /hr	5040
	m ³ /s	1.4
Max Length of Duct	m	15
Max Air Throw	m	15

SOUND DATA

Sound Pressure Level at 10 metres (ISO3744)	dB(A)	64
---	-------	----

PHYSICAL DATA

Overall Length	mm	1500
Overall Width	mm	750
Overall Height	mm	2250
Weight	kg	600

CONTACT US

Call us free on
0800 840 4210 or
visit our website
www.icscoolenergy.com

Depots Nationwide

hire@icscoolenergy.com

E&OE. All data is subject to change and continuous improvement without notice. Equipment designed to ISO 9001 and all relevant electrical, pressure and mechanical directives.

© ICS Cool Energy. All rights reserved.

**THE TEMPERATURE CONTROL SPECIALISTS.
SALES. HIRE. SERVICE.**

WWW.ICSCOOLENERGY.COM